

HCMM2-V HDMI Cable

4K 60Hz PVC High Speed HDMI® Cable with Ethernet VW-1 Rated



Overview

This HDMI cable supports Ultra HD video resolutions up to 4K for crystal-clear picture and sound. It also supports HDR (High Dynamic Range) for higher contrast ratio and vivid colors. Simultaneously contacts are gold-plated to resist corrosion and increase electrical conductivity and enhance durability.

High-quality PVC materials ensure outstanding performance throughout the cable's lifetime. Double shielding reduces line noise (EMI/RFI) that can disrupt signals traveling through the HDMI cord. This 4K HDMI cable is securely used for the home or general office environment.

Benefits

- Supports UHD Resolutions up to 4K (4:4:4) for Crystal-clear Video
- Al-Mylar Foil Shield and Gold-plated Contacts Improve Signal Integrity and Block External EMI
- Meet VW-1 Flame Retardant Grade, Suitable for Home or General Office Environment
- Carries High Dynamic Range (HDR) Signals for Rich Contrast and Expanded Color Accuracy
- Plug-and-play Operation without Software Required for Easy, Immediate Installation

Technical Specification

HDMI cables are compatible with our existing HDMI device interfaces and provide ultra-high-speed 2.0 version, supporting higher bandwidth transmission. Here's a look at the details.

CHARACTERISTICS

OVERVIEW	
UPC Code	
Product Type	Passive Cable
Technology	HDMI
Cable Type	Passive
VIDEO	
Max Supported Video Resolution	3840 x 2160 (4K) @ 60Hz
Max Supported Color Depth	24-bit True Color
HDR Support	Yes
3D Video Supported	Yes
Chroma Sub Sampling	4:4:4
EDID Support	Yes
Signal Transmission	Bidirectional
AUDIO	
Audio Specification	Stereo Audio
CONNECTIONS	
Side A - Connector 1	HDMI (MALE)
Side B - Connector 1	HDMI (MALE)
Connector Plating	Gold
Contact Plating	Gold
Connector Style	802.1X, AAA
ARP Table	Straight
Latching or Gripping Connector	No
PHYSICAL	
Color	Black

Cable Jacket Color	Black
Connector Color	Black
Cable Jacket Material	PVC
Cable Jacket Rating	VW-1
Cable Outer Diameter (OD)	7.3mm
Wire Gauge (AWG)	28
Cable Length (ft.)	9.84
Ferrite Core	No
Minimum Bend Radius	73mm
Shipping Dimensions (hwd / in.)	8x 6.5x 0.8
Shipping Weight (lbs.)	0.396
Unit Dimensions (hwd / in.)	8x 6.5x 0.8

ENVIRONMENTAL

Operating Temperature Range	32° to 113°F (0° to 45°C)
Storage Temperature Range	-40° to 176°F (-40° to 80°C)

COMMUNICATIONS

Consumer Electronics Control (CEC) Supported	Yes
--	-----

FEATURES & SPECIFICATIONS

EMI/RFI Line Noise Protection	Yes
MST Support	No
IP68 Rated	No
IP20 Rated	No
Armored Cable	No
Ethernet Support	No
HDCP Specification	1.4

STANDARDS & COMPLIANCE

Product Compliance	RoHS; REACH
--------------------	-------------